



# Novactsolv Blue LSF-H

## FUEL DYE SPECIALTY

Novactsolv Blue LSF-H is a single-phase liquid dye for the coloration of fuel, fuel additives. Lubricating oils, brake fluids and other petroleum based products.

### DYE CHEMICAL COMPOSITION

<b>Chemical Structure</b>				
<b>Chemical Family</b>	Anthraquinone			
<b>C.A.S. Number</b>	71819-49-3/74499-36-8			
<b>Empirical Formula</b>	N/A			
<b>Molecular Weight</b>	N/A gr/mol			
<b>EINECS</b>	N/A			
<b>Solvent System</b>	Solvent Naphtha CAS # 64742-84-5 <70%			
<b>Typical Properties</b>	Specific Gravity	1.0 - 1.1 at 68°F		
	Pounds per Gallon	8.3 approx.)		
	Physical appearance	Blue Liquid		
	Flash point	> 93.3°C (200°F) Method Pensky Martens Closed Cup		
	Vapor pressure	>0.1@37.8°C (100°F) (mmHg@20°C/68°F)		
	Brookfield Viscosity	5 20 cSt @ 40°C (104°F)		
	Color Strength	100% of N.C. Standard		
	Odor	Practically odorless		
<b>Hazards identification</b>	OSHA hazards	No known OSHA hazards		
	HMIS Classification	Health 1	Flammability 1	Reactivity 0
	Transportation Information	<b>DOT (US)</b>		<b>IMDG</b>
		Not dangerous	Not dangerous	Not dangerous
Flammability Classif.	OSHA Combustible Liquid IIIB			
<b>Dosage</b>	Fuels	5 – 20 mg/l		
	Lubricants	50 to 200 mg/l		
	Greases	500 to 2000 mg/l		

All technical data, recommendations and service are accurate to the best of our knowledge. Novact Corporation assumes no responsibility for the results obtained or damage incurred from use by the buyer in whole or in part since method of application and its use is beyond our control. It is the responsibility of the user to test the suitability of the products under their processing conditions. The information on this Technical Bulletin does not constitute a product specification.